



CONDENSER MICROPHONE PA 58

This microphone is useful for platforms and rostrum, not to mention an altar and pulpet in the church. High flexibility is possibly by the extension tube and two short goosenecks.

The microphone is also made for Floor Stand, model **PA 58G**. In this case the gooseneck is mounted at a 70 cm extension tube fitted with a 3/8" thread. This attachment can be mounted at our Floor Stand 1220.

The model **PA 58 AMP** have the preamp at the bottom of the gooseneck and an integrated 3-pin male XLR for connection to a socket connector.

One another model; **PA 58 H** with the cable direct from the microphone head, may well be used for hanging.

A 90 degree angle can be obtained by the hook 5425.

The cable between microphone and preamplifier (with a 3-pin XLR integrated) is 10 metres.

Finished in black or white powder paint.

Accessories:

Table stand	1203
Table mounting flange 3/8"	1207
Extension pole 100mm 3/8"-3/8"	1209
Telescopic stand 40-60cm	1220
Hook (for model PA 58-H)	5425
Windscreen	1720

Specification:

Pattern:	Cardioid
Operation Voltage:	15-48V
Sensitivity:	12mV/Pa
Max SPL:	120 dB
Self Noise:	19 dB
Current consumption:	1,3 mA
Rec. Min. load imp:	1 Kohm
Dimension head:	Ø 18x30 mm
Dimension, preamp	Ø 19x95 mm

