



1910  
Shock-proof  
Boom Mount

E-5410/S

**PML**<sup>®</sup>  
from  
Sweden

E-5410

## ACCESSORIES FOR TC-4 STUDIO CONDENSER MICROPHONES

Type	Description
5406.....	20 ft. 5 conductor cable fitted with locking connectors to mate microphone to power supply. (Supplied with microphone)
5406/30....	30 ft. 5 conductor extension cable to extend distance of mike / power supply to total of 50 ft. Fitted with locking connectors.
5406/80....	80 ft. extension as above to extend to 100 ft.
5425.....	20 ft. 5 conductor cable fitted with locking connectors to mate microphone to power supply. For US models. (Supplied with microphone)
5425/30....	30 ft. 5 conductor extension cable to extend distance of mike / power supply to total of 50 ft. Fitted with locking connectors. For US models.
5425/80....	80 ft. extension as above to extend to 100 ft. For US models.
E-5410.....	Mains operated (110-220 V. 50/60 cycles A.C.) power supply with 6 ft. line cord. Fitted with locking sockets. 6" L x 4 3/4" W x 1 5/8" H. Wt. 30 oz.
E-5410/S...	As above, but to power 2 microphones in stereo or mono mode. 6" L x 4 3/4" W x 1 5/8" H. Wt. 32 oz.
5403.....	20 ft. 2 conductor (plus shield) coaxial signal cable. Fitted with locking connector at one end, alternate unterminated. Supplied with E-5410. Two supplied with E-5410/S.
5403/50....	50 ft. 2 conductor (plus shield) coaxial signal cable. Fitted with locking connector at one end, alternate unterminated.
5403/100...	100 ft. signal cable as above.
5210.....	Stand adaptor (5/8" x 27 T.P.I.) To fit TC-4, TC-4B, TC-4K, TC-4V to microphone stand. (Supplied with microphone).
1910/27....	Shock-proof boom mount with ball joint and nipple (5/8" x 27 T.P.I.) for TC-4, TC-4B, TC-4K, TC-4V)
1910/43....	As above, but for TC-4US types. (Supplied with microphone)

SOLD & RECOMMENDED BY:

**ERCONA**  
**CORPORATION**  
432 PARK AVENUE SO.  
NEW YORK, N. Y. 10016